

NAME	
DATE	
TRACK	
EVENT	

PINION		TRANSMISSION		SPUR *60T/55T(Only for OS12TG)	
☐ 15T	☐ 16T	☐ 17T	☐ 1ST	☐ 57T	☐ 58T
☐ 20T	☐ 21T	☐ 22T	☐ 2ND	☐ 52T	☐ 53T
				☐ 54T	☐ 55T

SIDE PULLEY	
☐ 25T(STD)	☐ 26T(OPT)

FRONT SHOCKS		REAR	
☐ SHORT	☐ STD	☐ SHORT	☐ STD
☐ High ☐ Low SPRING&RETAINER		☐ High ☐ Low	
#	OIL	#	
☐ STD	☐ OPTION	☐ STD	☐ OPTION
☐ STD	☐ OPTION	☐ STD	☐ OPTION
MEMBRANE		PISTONS	
HOLE(S) _____ SHAFT _____ LENGTH _____ mm		HOLE(S) _____ SHAFT _____ LENGTH _____ mm	

FRONT DIFF		REAR	
☐ HIGH	☐ #	☐ HIGH	☐ #
☐ LOW		☐ LOW	
☐ AL COVER(G228)		☐ AL COVER(G306)	

FRONT ANTI-ROLL BAR		REAR	
mm		mm	

FRONT RIDE HEIGHT		REAR	
mm		mm	

FRONT WIDTH		REAR	
mm		mm	

TIRES		CONTROLLED	
BRAND		☐ YES ☐ NO	
LEFT	FRONT	RIGHT	
mm	mm	mm	mm
DIAMETER			

FRONT WHEEL PLATE		REAR	
☐ YES	☐ NO	☐ YES	☐ NO

HEX HUB		U (Universal) / D (Drive Shaft)	
☐ STD	☐ OPT		
☐ OPT (LARGE)			
		FRONT REAR ☐ 90° U(OPT) ☐ 90° U(OPT) ☐ 0° D(OPT) ☐ 0° U(STD) ☐ 0° U(STD) ☐ 0° U(50mm) ☐ 0° U(50mm) ☐ 0° U(AL51mm) ☐ 0° U(AL52mm) ☐ AL JOINT(G303) ☐ 90° U(AL51mm) ☐ 90° U(AL52mm) ☐ AL JOINT(G303)	

WHEEL SHAFT		BODY	
FRONT	REAR	TYPE	
☐ STD	☐ STD	POSITION	
☐ LIGHT	☐ LIGHT	WING	

☐ STD	☐ CARBON
------------------------------	---------------------------------

BUMPER HOLE	

FRONT	CENTER	REAR
☐ HARD(TS013) ☐ STD(G003)	7 6 5 4 3 2 1 NO	mm mm

CASTER		SHOCK TOWER	
mm		G185 (STD) G215 (SHORT) G279 (USP2)	
SPACER		KNUCKLE PLATE	
mm		☐ G187 ☐ G278 POS	
TOE OUT		UPPER SHIM	
deg.		mm	

LOWER SUS HOLDER		UPPER POSITION	
☐ BLACK		mm	
MATERIAL		CAMBER	
KNUCKLE ☐ OLD(G008) ☐ NEW(G288) ☐ HARD(G008H)		deg.	
UPPER ARM ☐ STANDARD ☐ HARD		DOWN STOP	
LOWER ARM ☐ STANDARD ☐ HARD		mm	

WHEEL BASE SHIM		SHOCK TOWER	
mm		G183 (STD) G155 (SHORT) G280 (USP2)	
SPACER		UPPER POS	
mm		☐ IN ☐ OUT deg.	
TOE IN		CAMBER	
deg.		deg.	

SUS BLOCK POS		SUS COVER	
☐ STANDARD ☐ WIDE (G076/G077)		☐ NO ☐ STANDARD ☐ HARD ☐ CARBON	
SPACER		MATERIAL	
mm		SUS ARM ☐ STANDARD ☐ HARD REAR HUB ☐ OLD(G009B) ☐ NEW(G289) ☐ HARD(G009BH)	
SCREW POINT		DOWN STOP	
		mm	

SERVO SAVER		CENTER BULK	
8 POS 9 10 11 ☐ STD ☐ AL ☐ HYBRID(G272)		☐ STD ☐ AL	
UPPER STIFFENER		WEIGHT	
☐ YES ☐ NO		1 2 3 4 5 6 7 8 9.5g 14g 20g 28g	

CENTER STIFFENER		REAR CHASSIS STIFFENER	
☐ YES ☐ NO		☐ CARBON(G230) ☐ NO ☐ STAINLESS(G286)	

COMMENT	